C516 ML



PROFESSIONAL MINIATURE CONDENSER INSTRUMENT MICROPHONE



HIGHLIGHTS

Cardioid polar pattern for problem-free use with high ambient noise rejection

Flexible shock mount for efficient suppression of mechanical and body noise

Rugged, highly stable goose-neck for precise placement of the microphone

Detachable microphone cable easy to install and service

Established as an industry-standard accordion mic on stages worldwide, day by day for decades

KEY MESSAGE

The C516 ML professional miniature instrumental microphone, part of the MicroMics family, is designed for use on accordions, pianos, guitar speakers and keyboard/organ cabinets. Using two C516 MLs (one on the bass and one on the treble side) and an optional B23 L battery power supply is the ideal way to mic up an accordion.

The C516 ML comes with a wide variety of mounting materials, such as screws, adhesive pads and adapter plates, for easy installation on the instrument or amp.

CUT SHEET

C516 ML

PROFESSIONAL MINIATURE CONDENSER INSTRUMENT MICROPHONE



APPLICATIONS

ACCORDIONS Guitars Pianos

TECHNICAL SPECIFICATIONS

Audio frequency bandwidth: Equivalent noise level: Sensitivity: Signal to Noise: Electrical impedance: Recommended load impedance: Polar Patterns:	60 to 20000 Hz 31 dB-A 5 mV/Pa 63 dB-A 200 Ohms 2000 Ohms Cardioid
Powering Interface Voltage: Current:	2 to 12 V 2 mA
Audio Output Type: Gender: Contacts:	Mini XLR Female 3-pin
Design Body: Finish:	Metal Matte Black
Dimensions/Weight Height:	47mm



INCLUDED ACCESSORIES

Diameter:

Net Weight:

 A400 Adapter Plate
 Double-Sided Adhesive Rubber Plate
 H516 Mount Plate
 Self-Tapping Screws (2.9 x 13mm)

 Countersunk Bolts (3x 30mm)
 Microphone Bag
 W44 Windscreen



AKG ACOUSTICS, U.S. 8400 BALBOA BOULEVARD, NORTHRIDGE, CA 91329, U.S.A. AKG ACOUSTICS GMBH LAXENBURGER STRASSE 254, 1230 VIENNA, AUSTRIA

© 2017 HARMAN International Industries, Incorporated. All rights reserved. AKG is a trademark of AKG Acoustics GmbH, registered in the United States and/or other countries. Features, specifications and appearance are subject to change without notice.

235mm

46 g